

AIR SOURCE HEAT PUMPS

ASHP SOAK-AWAY

THIS UNIQUE PRE-BAGGED GEO TEXTILE SOAKAWAY IS USED TO SAFELY DISPOSE OF THE CONDENSATE FROM ALL DOMESTIC SIZED AIR SOURCE HEAT PUMPS WHERE DRAIN ROUTING IS NOT AVAILABLE.

THE VOLUME OF CONDENSATE CREATED FROM AN AIR SOURCE HEAT PUMP UP TO 16KW CAN BE BETWEEN 10-15 LITRES PER HOUR UP TO 2000 LITRES PER YEAR.

- ALTERNATIVE METHOD TO CONDENSATE REMOVAL DISPOSAL AND SUITABLE FOR ALL MODELS/BRANDS OF AIR SOURCE HEAT PUMPS
- MADE FROM PRE-BAGGED GEO-TEXTILE MATERIAL TO PREVENT SOIL INGRESS
- PRE FILLED WITH LIGHTWEIGHT GRANULES

▪ CAPACITY - 10-15 LITRES PER HOUR

▪ 32MM INLET



- THIS METHOD PREVENTS THE CONDENSATE FROM FLOWING ONTO PATHS AND DRIVEWAYS, WHICH CAN FREEZE AND CAUSE A SLIP HAZARD

PUMP
HOUSE

DIVERSITECH[®]
INTERNATIONAL

[in pump-house-ltd](#)

[pumphousepumps](#)

[@pumhouseLtd](#)

[@PumpHouseLtd](#)

[diversitechuk](#)

sales@diversitech.com
www.diversitech.global