

AIR SOURCE HEAT PUMPS

EXTERNAL TRUNKING

PIPEWORK AND INSULATION RUNNING FROM AN AIR SOURCE HEAT PUMP SHOULD BE PROTECTED. OUR RANGE OF TRUNKING COMES IN 140/150MM WIDTH (IVORY / BLACK) AND ACCOMMODATES BOTH THE INSULATED FLOW AND RETURN PIPEWORK AS WELL AS ANY ASSOCIATED CABLING.

- MADE FROM HIGH GRADE, UV STABLE, FADE RESISTANT PVC
- PROTECTION FROM ELEMENTS, ACCIDENTAL DAMAGE & PEST/HUMAN VANDALISATION
- PROVIDES A PROFESSIONAL AND NEAT FINISH ON YOUR INSTALLATION



▪ WHY LEAVE YOUR INSTALL LOOKING LIKE THIS?



▪ WHEN IT CAN LOOK LIKE THIS



▪ BLACK



▪ IVORY

PUMP
HOUSE

DIVERSITECH[®]
INTERNATIONAL

[in pump-house-ltd](#)

[pumphousepumps](#)

[@pumphouseltd](#)

[@PumpHouseLtd](#)

[diversitechuk](#)

sales@diversitech.com
www.diversitech.global