## ADJUSTABLE FOOT TECHNICAL DATA SHEET



## ■ BABY SUMO RUBBER SUPPORT FOOT






These mini adjustable feet are perfect as ground supports for AC and ASHP units. They are made from reprocessing discarded tyres where 70-95% of the rubber can be recovered. These feet are made of a blend of SBR vulcanised UV-stable rubber with internal glass fibrereinforced polypropylene.


### ■ IN THE BOX

- Integral M10 bolt with nut and washer
- NBR rubber anti-vibration washer
- Integral spirit level

## **FEATURES**

- Anti-vibration mount made of UV-stabilised rubber compound
- Suitable for supporting units on uneven or sloping surfaces
- Adjustable height between 160-210mm
- NBR rubber washer at the fixing point to further reduce vibration
- The support surface features a substantial contact area offering a stable and secure base
- Solid structure prevents water stagnation and seepage
- Working temperature: -30°C / +75°C





Part code	Description	Height (B)	Width (A)	Depth (C)	Safe working load	Fixing (D)	QTY
SUMO-FT	Mini adjustable foot	160-210mm	160mm	160mm	150kg (per foot)	M10	Pack of 4
SUMO-FT-6	Mini adjustable foot	160-210mm	160mm	160mm	150kg (per foot)	M10	Pack of 6

#### Materials:



#### Support:

- SBR vulcanised rubber, made by recycling discarded car tyres
- PP glass fibre reinforced polypropylene

#### Fixing kit:

• Steel 4.8 DIN 933-8.8 with electro zinc-plating 7-8 µm EN ISO 12329 (integral nut and bolt)

#### Anti-vibration washer:

NBR Rubber

# SUPPORT HEIGHT ADJUSTABLE FOOT

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East Nottingham NG8 4LY United Kingdom