

■ SPEEDIDUCT EXTERNAL TRUNKING



- Made of rigid, shockproof, UV-stabilised fire resistant PVC B
- High-quality (usable from -20°C / -4°F to +60°C / 140°F in a static position)
- The inside fixation rail (SpinFix) allows you to use cable ties to strap and keep the linesets in place - contributing to the duct rigidity



■ DUCT



| Description | Width | Black Part code |
|-------------------------------------|-------|-----------------|
| SpeediDuct trunking (2000mm length) | 150mm | TR-D-150-B |

■ CONNECTION PIECE



| Description | Width | Black Part code |
|-----------------------------|-------|-----------------|
| SpeediDuct Connection piece | 150mm | TR-CP-150-B |

■ FLAT BEND



| Description | Width | Black Part code |
|----------------------|-------|-----------------|
| SpeediDuct flat bend | 150mm | TR-FB-150-B |

■ WALL COVER



| Description | Width | Black Part code |
|-----------------------|-------|-----------------|
| SpeediDuct wall cover | 150mm | TR-WC-150-B |

TRUNKING AIR SOURCE HEAT PUMPS

EXTERNAL 150MM TRUNKING

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call **+44 (0)115 900 5858** or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global



Glaisdale Drive East
Nottingham NG8 4LY
United Kingdom