



## TYPE 2 (3 ARMS) BRACKETS



Also available in black

These flat-packed, self assembly brackets provide a professional finish to the installation of wall mounted outdoor condensing units and air source heat pumps. The Type 2 brackets have a crossbar allowing the uprights to be spaced exactly as required, and include wall spacers to help level the unit on uneven walls. All components receive a powder coating, with a scratch resistant, textured finish in a colour (RAL 7032) to match most brands of condensing units and domestic air source heat pumps.

### FEATURES

- Integral spirit level for easier, correct installation
- Uprights mount anywhere on the crossbar which enables the arm span to be adjusted easily
- Adjustable wall spacers to level the arms
- Safe working load up to 250kg
- Suitable to match most brands of condensing units and domestic air source heat pumps
- Extra long arms (up to 660mm available for larger condensing units)
- Textured finish in (RAL 7032)

### THE PACKAGE

- Crossbar with spirit level
- 2 x support arms
- 2 x uprights
- Fixings
- Installation instructions

### RELATED PRODUCTS


- All guards
- Collection trays

NB: Sea salts are very corrosive and affect both ferrous and non-ferrous metals. Coastal installations are particularly at risk as they are frequently exposed to sea salt solutions followed by dry periods, where this wet/dry cycle produces a very corrosive environment. We strongly recommend that in such locations only our stainless steel brackets are installed.

### WEATHER PROTECTION PROCESS



**PROCESS ONE**  
Corrosion resistant raw material, often referred to as Zintec



**PROCESS TWO**  
Zinc phosphating process multi stage cleaning and dipping chemical zinc



**PROCESS THREE**  
ED coating process: electrophoretic deposition (aka ED or EPD) coating



**PROCESS FOUR**  
Epoxy polyester powder coating

| Part code        | Description                         | Safe working load* | Max load | Crossbar | Upright | Support arm | Weight |
|------------------|-------------------------------------|--------------------|----------|----------|---------|-------------|--------|
| CBR2-XL-3A       | Type 2 Bracket – XL (3 arms)        | 250kg              | 500kg    | 1040mm   | 550mm   | 660mm       | 16.2kg |
| CBR2-XXL-3A-BL-D | Type 2 Bracket – Double XL (3 arms) | 200kg              | 400kg    | 1120mm   | 550mm   | 780mm       | 17.3kg |

\*All brackets are tested to twice the safe working loads at an independent UK facility.

## BRACKETS TYPE 2 BRACKETS

(3 arms)

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to [sales@diversitech.com](mailto:sales@diversitech.com) or visit [www.diversitech.global](http://www.diversitech.global)