



■ ROTARY ENCLOSED ISOLATORS



Insulated 3 and 4 pole, CE marked, A/C isolators, suitable for disconnecting power supply to outdoor air conditioning condensing units. Available in standard, small and with cable gland.

■ FEATURES

- Weatherproof to IP65
- Easy installation
- M20/25 knockouts up to 63A
- Handle lockable in off position
- Interlocked cover - removable in off position only
- Earth and neutral terminals included
- Captive, retained cover screws
- Conforms to IEC 60947-3

■ THE PACKAGE

- Rotary Enclosed Isolator

■ RELATED PRODUCTS

- All Guards
- All Brackets

Part code	No of poles	Part code (WITH GLAND)	AMPS AC21	AC23 A 240VA	AC23 A 400VA	Cable capacity		Height	Width	Depth
						Solid	Stranded			
IS-3P-20A-S	3	IS-3P-20A-S-G	20amp	5.5kW	3.7kW	1-16mm ²	0.75-10mm ²	125mm	100mm	120mm
IS-3P-32A-S	3		32 amp	11kW	7.5kW	1-16mm ²	0.75-10mm ²	125mm	100mm	120mm
IS-3P-20A	3	IS-3P-20A-G	20amp	5.5kW	3.7kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-32A	3	IS-3P-32A-G	30amp	11kW	7.5kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-40A	3	IS-3P-40A-G	40amp	15kW	11kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-3P-63A	3	IS-3P-63A-G	63amp	22kW	18.5kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-20A-S	4		20amp	5.5kW	3.7kW	1-16mm ²	0.75-10mm ²	125mm	100mm	120mm
IS-4P-32A-S	4	IS-4P-32A-S-G	32 amp	11kW	7.5kW	1-16mm ²	0.75-10mm ²	125mm	100mm	120mm
IS-4P-20A	4		20amp	5.5kW	3.7kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-32A	4	IS-4P-32A-G	32amp	11kW	7.5kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-40A	4	IS-4P-40A-G	40amp	15kW	11kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm
IS-4P-63A	4	IS-4P-63A-G	63amp	22kW	18.5kW	1-16mm ²	0.75-10mm ²	175mm	114mm	135mm

ACCESSORIES ISOLATORS

Rotary Enclosed Isolators

The DiversiTech International sales team are available to answer your questions or queries on this product. Our experts are waiting for your call +44 (0)115 900 5858 or if you prefer send an email to sales@diversitech.com or visit www.diversitech.global