





THIS THERMOMETER IS THE FIRST IN THE INDUSTRY TO ATTACH TO ANY MANIFOLD.




DUAL READOUT THERMOMETER

Measuring system temperature requires multiple tools, and sometimes multiple trips to the truck. The Hilmor Dual Readout Thermometer was designed to change that. It's the industry's only manifold-compatible compact thermometer with two readings to make calculations simple. You can use it on any manifold. You can use it independently. But most important, you can use it to maximize efficiency. Sold with two K-style thermocouple clamps.

- 

MAKES CALCULATIONS EASIER
THE INDUSTRY'S ONLY MANIFOLD COMPATIBLE COMPACT THERMOMETER WITH TWO READINGS TO HELP SIMPLIFY THE CALCULATION OF SUPERHEAT AND SUBCOOL.
- 

SUPERIOR VERSATILITY
USE IT ON ANY GAUGE SET, OR REMOVE IT AND USE IT INDEPENDENTLY.
- 

READS TEMPERATURES QUICKLY
TWO EASY-TO-USE, K-STYLE TUBECLAMP THERMOCOUPLES GET YOU TO THE TEMPERATURE READING QUICKLY.

TWO THERMOCOUPLES INCLUDED	1839108 TCC THERMOCOUPLE CLAMP
BATTERIES	AA X 1 (INCLUDED)
BATTERY LIFE	151 HOURS
CONNECTION TYPE	K
MEASUREMENT	TEMPERATURE
RANGE	-76°F TO 999.9°F
RESOLUTION	.10° F/C
ACCURACY	+2.0 C°/+3.6°F
OPERATING TEMPERATURE RANGE	0°C TO +50°C (LCD)

Part code	Description	Length	Width	Height	Weight
1839106	DROT2TCC DUAL READOUT THERMOMETER	1-3/4"	1-5/8"	3-7/8"	11 oz